



150W, 120W, 90W, 3CCT adjustable LED highbay with F&P

HBY24-150W-4-PA-CCT



Introducing our innovative high-bay light fixture, designed to meet your lighting needs in warehouses, factories, gymnasiums, logistics centers, corridors, and more. Our high-bay light features a unique "UFO" heatsink design, providing excellent thermal dissipation to ensure long-lasting, efficient operation. Invest in our high-bay light fixture and experience the benefits of superior lighting performance, increased efficiency, and reduced maintenance costs.

Features & Benefits

- Unique "UFO" heatsink design with excellent thermal dissipation
- High efficiency SMD LED chips can reach 170lm/w (at 5000K)
- Lightweight, rugged die cast aluminum housing
- Shatterproof polycarbonate lens cover
- Built in Remote Controlled Microwave Sensor (Optional)
- 3CCT and 3Wattage selectable by DIP switch
- Accessories can be customized to meet specific needs, providing versatility and flexibility for different applications.
- Accessories: Dust cover, PC cover, emergency kit, U bracket can be assembled and sold separately
- Quick and easy installation saves time and effort
- 50,000 hour lifespan provides long lasting, reliable performance

- 5 year warranty ensures peace of mind and protection against defects
- Selectable CCT and Wattage reduces the need for multiple SKUs, saving on capital and warehouse investment and accelerating cash flow

150W, 120W, 90W, 3CCT adjustable LED highbay with F&P

HBY24-150W-4-PA-CCT

Specifications

SKU	HBY24-150W-4-PA-CCT
Luminaire efficacy	170 lm/W
EAN	9359682002736
Weight	3.2
Light Colour	3CCT
Wattage	90/120/150 W
Lumen output	15367, 20288, 24954 lm
IP rating	65
IK Rating	10
CRI	70
Beam Angle	120 Degrees
Trim colour	Black
Diameter	290 mm
Height	170 mm
Lifespan	50000 Hours
Warranty	5 Years
Dimmable	Dimmable
Constant current/voltage	Constant Current
Shatterproof	Shatterproof
Mounting type	Hook, Wall Bracket, Pole
LED source	H Great
Accessories	Optional Microwave Sensor Wall Bracket
Lamp Type	LED
Dimming	0-10V
Input voltage	100V 240V AC
Diffuser	Transparent
Wiring method	Flex & Plug or Hardwire
Weatherproof	Weatherproof
Working temperature	30° to 45°
Box Qty	1
Pallet Qty	70
Kelvin	6000K/5000K/4000K
Power Adjustable	Yes



Dimensional Drawings

Photometric information available upon request.

Please note: This product is Power Adjustable between 150W,

120W, 90W & is 3CCT.