

MAJOR COLLECTION

SKU: MAJOR-COLLECTION











QUOTE: PROJECT: TYPE:

Introducing our innovative high-bay light fixture, designed to meet your lighting needs in warehouses, factories, gymnasiums, logistics centers, corridors, and more. Our high-bay light features a unique "UFO" heatsink design, providing excellent thermal dissipation to ensure longlasting, efficient operation Invest in our high-bay light fixture and experience the benefits of superior lighting performance, increased efficiency, and reduced maintenance costs.

Features & Benefits

- \bullet Unique "UFO" heatsink design with excellent thermal dissipation
- $\,^{\circ}$ High efficiency SMD LED chips can reach 170lm/w (at 5000K)
- •Lightweight, rugged die cast aluminum housing
- Shatterproof polycarbonate lens cover
- •Built in Remote Controlled Microwave Sensor (Optional)
- •3CCT and 3Wattage selectable by DIP switch
- •Accessories can be customized to meet specific needs, providing versatility and flexibility for different applications.
- •Accessories: Dust cover, PC cover, emergency kit, U bracket can be assembled and sold separately
- •Quick and easy installation saves time and effort
- •50,000 hour lifespan provides long lasting, reliable performance
- •5 year warranty ensures peace of mind and protection against defects
- •Selectable CCT and Wattage reduces the need for multiple SKUs, saving on capital and warehouse investment and accelerating cash flow

PRODUCT IMAGE







MAJOR COLLECTION


SKU: MAJOR-COLLECTION

PRODUCT IMAGES & DIMENSIONS



×

HBY24-150W-4-5K



SPECIFICATIONS

SKU	HBY24-150W-4-5K	HBY24-150W-4-PA-CCT
Luminaire efficacy	150 lm/W	170 lm/W
Weight		3.2
Light Colour	Natural White	3CCT
Wattage	150 W	90/120/150 W

www.gentechlighting.com.au

Lumen output	22500 lm	15367, 20288, 24954 lm
IP rating	65	65
IK Rating		10
Beam Angle	120 Degrees	120 Degrees
Trim colour	Black	Black
Diameter	mm	290 mm
Height	123 mm	170 mm
Lifespan	50000 Hours	50000 Hours
Warranty	5 Years	5 Years
Dimmable	Dimmable	Dimmable
Shatterproof	Shatterproof	Shatterproof
Mounting type	Hook,Surface	Hook, Wall Bracket, Pole
Accessories		Optional Microwave Sensor Wall Bracket
Lamp Type	LED	LED
Dimming	0-10V	0-10V
Input voltage	240 Volt AC 50HZ	100V 240V AC
Diffuser	Transparent	Transparent
Wiring method	Flex & Plug or Hardwire	Flex & Plug or Hardwire
Weatherproof	Weatherproof	Weatherproof
Working temperature	30° to 45°	30° to 45°
Box Qty	1	1
Kelvin	5000K	6000K/5000K/4000K