



1.5W SOLAR BOLLARD CCT SWITCHABLE

VBLBOS-022-4-CCT



Our VBLBOS-022 Series colour switchable solar bollard. This popular bollard is equipped with a high capacity 3.2V 12AH of LiFePO4 battery pack and high-efficiency MONO solar panel. The LiFePO4 battery pack is well integrated inside of the light head as a complete unit and connects to the control board with DC connectors which makes the replacement or repair work much easier. The big battery pack is able to produce sufficient light output for 3-4 days without charging, once fully charged. Wireless remote can control all the light heads within up to 30 meters in the open air.

Features & Benefits

- Built in Solar Panel charges throughout the day and uses stored energy during the night
- Automatic day and night sensor installed
- Fast charging Lithium LiFePo4 Battery
- Seaside Resistant, Corrosion Resistant
- Replacement Batteries available
- IP65 rated
- 50,000 hour lifespan
- 2 Year Warranty



1.5W SOLAR BOLLARD CCT SWITCHABLE

VBLBOS-022-4-CCT

Specifications

| SKU | VBLBOS-022-4-CCT |
|---------------------|-------------------|
| Luminaire efficacy | 173 lm/W |
| EAN | 9340994029702 |
| Weight | 5.2 |
| Light Colour | 3CCT |
| Wattage | 1.5 W |
| Lumen output | 260 lm |
| IP rating | 65 |
| IK Rating | 8 |
| Beam Angle | 180 Degrees |
| Trim colour | Black |
| Width | 255 mm |
| Height | 900 mm |
| Lifespan | 50000 Hours |
| Warranty | 2 Years |
| Dimmable | Non-Dimmable |
| Mounting type | Surface |
| LED source | SMD2835 |
| Material | Die Cast Aluminum |
| Lamp Type | LED |
| Weatherproof | Weatherproof |
| Working temperature | -15°C ~ +45°C |
| Box Qty | 1 |
| Pallet Qty | 32 |
| Kelvin | 3000K/4000K/6000K |
| | |

Photometric information available upon request.



Dimensional Drawings

