



167 - WIZ SMART Downlight

VBLDL-167-1-WIZ



Using the newest smart lighting technology, our 10W White WIZ LED Downlight can be voice operated through Alexa, Siri and Google Home, as well as controlled through a versatile mobile App. Perfect for domestic applications, this light provides colour temperature ranges from 2600K-6500K, for such a small light, it offers an impressive lumen output of 700lm. Comes with an easy to install flex & plug, and a 60° beam angle. Accessories available include Black and Brushed Chrome trim. Includes a 50,000 hour lifespan and 3 year warranty.

Features & Benefits

- Using the newest smart lighting technology, the WIZ downlight can be voice operated through Alexa, Siri and Google Home, as well as controlled through a versatile mobile App
- Equipped with CITIZEN LED chips
- Colour temperature ranges from 2600K-6500K, with an impressive lumen output of 700lm for such a small light
- IC-4 Rated Fitting ONLY, excludes driver
- \bullet Comes with an easy to install flex and plug & 60° beam angle
- White, Black and Brushed Chrome trim available
- 50,000 hour lifespan
- 3 year warranty




Specifications

Luminaire efficacy 70 lm/W EAN 9340994021232 Light Colour CCT Wattage 10 W Lumen output 700 lm IP rating 65 CRI 80 Beam Angle 60 Degrees Trim colour White Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Constant current/voltage Mounting type Recessed Accessories Also available in Black or Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming	SKU	VDI DI 167 1 WIZ
Light Colour CCT Wattage 10 W Lumen output 700 Im IP rating 65 CRI 80 Beam Angle 60 Degrees Trim colour White Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Constant current/voltage Mounting type Recessed Accessories Lamp Type LED Dimming Tool Im CCT White CCT 10 W 10 W 10 W 10 W 10 W 10 Im 10 W 10 Im 10 I		VBLDL-167-1-WIZ
Light Colour Wattage Lumen output 700 lm IP rating 65 CRI 80 Beam Angle 60 Degrees Trim colour White Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Constant current/voltage Mounting type Accessories Also available in Black or Brushed Chrome trim. LED Dimming Triac Dimming	Luminaire efficacy	70 lm/W
Wattage 10 W Lumen output 700 lm IP rating 65 CRI 80 Beam Angle 60 Degrees Trim colour White Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Constant current/voltage Recessed Accessories Also available in Black or Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming	EAN	9340994021232
Lumen output IP rating 65 CRI Beam Angle 60 Degrees Trim colour White Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Constant current/voltage Mounting type Accessories Lamp Type LED Dimming 700 lm 700 lm Constant Current Current Current Constant Current Cu	Light Colour	CCT
IP rating 65 CRI 80 Beam Angle 60 Degrees Trim colour White Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Constant current/voltage Mounting type Recessed Accessories Also available in Black or Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming	Wattage	10 W
CRI 80 Beam Angle 60 Degrees Trim colour White Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Constant current/voltage Constant Current Mounting type Recessed Accessories Also available in Black or Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming	Lumen output	700 lm
Beam Angle 60 Degrees Trim colour White Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Constant current/voltage Constant Current Mounting type Recessed Accessories Also available in Black or Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming	IP rating	65
Trim colour Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Constant current/voltage Mounting type Accessories Lamp Type LED Dimming White 70 mm Constant Current Survent Accessories LED Triac Dimming	CRI	80
Cut out 70 mm Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Constant current/voltage Constant Current Mounting type Recessed Accessories Also available in Black or Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming	Beam Angle	60 Degrees
Diameter 85 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Constant current/voltage Constant Current Mounting type Recessed Accessories Also available in Black or Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming	Trim colour	White
Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Constant current/voltage Mounting type Recessed Accessories Also available in Black or Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming	Cut out	70 mm
Warranty Dimmable Constant current/voltage Mounting type Accessories Lamp Type Dimming Dimmable Constant Current Accessed Also available in Black or Brushed Chrome trim. LED Dimming Triac Dimming	Diameter	85 mm
Dimmable Constant current/voltage Mounting type Accessories Lamp Type Dimming Dimmable Constant Current Recessed Also available in Black or Brushed Chrome trim. LED Triac Dimming	Lifespan	50000 Hours
Constant current/voltage Mounting type Recessed Accessories Accessories Lamp Type LED Dimming Constant Current Accessed Also available in Black or Brushed Chrome trim. LED Triac Dimming	Warranty	3 Years
Constant Current Mounting type Recessed Accessories Accessories Lamp Type LED Dimming Constant Current Recessed Also available in Black or Brushed Chrome trim. LED Triac Dimming	Dimmable	Dimmable
Accessories Also available in Black or Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming		Constant Current
Accessories Brushed Chrome trim. Lamp Type LED Dimming Triac Dimming	Mounting type	Recessed
Dimming Triac Dimming	Accessories	
	Lamp Type	LED
Input voltage 100V - 240V AC	Dimming	Triac Dimming
input voltage	Input voltage	100V - 240V AC
Wiring method Flex & Plug	Wiring method	Flex & Plug
Weatherproof Weatherproof	Weatherproof	Weatherproof
Working temperature $-20^{\circ}\text{C} \sim 45^{\circ}\text{C}$	Working temperature	-20°C ~ 45°C
Box Qty 30	Box Qty	30



Dimensional Drawings



Photometric information available upon request.