



25W 3CCT LED DOWNLIGHT

VBLDL-217-1-CCT



This white LED recessed downlight features adjustable color temperature and power settings, and is easy to install. Designed for indoor use with an IP44 rating, it offers a long lifespan of 50,000 hours and comes with a 3-year warranty.

Features & Benefits

- Versatile downlight, perfect for use in a wide range of applications
- Flex & Plug for quick and easy installation
- CRI 80
- IP44 Weatherproof
- 3CCT colour switchable: 3000K/4000K/5700K
- Power adjustable: 18W / 20W / 23W / 25W / 28W / 30W
- 3 Year Warranty
- 50,000 hr lifespan



Specifications

Luminaire efficacy Luminaire efficacy EAN 9340994031330 Weight 0.5 Light Colour Wattage 18/20/23/25/28/30 W Lumen output IP rating 44 CRI 80 Beam Angle 90 Degrees Trim colour White Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Output current 600 mA Constant current/voltage Shatterproof Mounting type LED Source Material Lamp Type Dimming Input voltage Diffuser Opal Wiring method Weatherproof Box Qty Pallet Qty Sa4 Kelvin SCCT 100 lm/W 2340994031330 0.5 6	•	
EAN 9340994031330 Weight 0.5 Light Colour 3CCT Wattage 18/20/23/25/28/30 W Lumen output 2282, 2594, 2506 lm IP rating 44 CRI 80 Beam Angle 90 Degrees Trim colour White Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Shatterproof Mounting type Recessed LED source SMD Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty 12 Pallet Qty 384	SKU	VBLDL-217-1-CCT
Weight 0.5 Light Colour 3CCT Wattage 18/20/23/25/28/30 W Lumen output 2282, 2594, 2506 Im IP rating 44 CRI 80 Beam Angle 90 Degrees Trim colour White Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Shatterproof Mounting type Recessed LED source SMD Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Weatherproof Box Qty 12 Pallet Qty 384	Luminaire efficacy	100 lm/W
Light Colour Wattage 18/20/23/25/28/30 W Lumen output 2282, 2594, 2506 lm IP rating 44 CRI 80 Beam Angle 90 Degrees Trim colour White Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Mounting type LED Source Material Lamp Type LED Dimming Input voltage Diffuser Opal Wiring method Weatherproof Weatherproof Box Qty Pallet Qty 384	EAN	9340994031330
Wattage 18/20/23/25/28/30 W Lumen output 2282, 2594, 2506 lm IP rating 44 CRI 80 Beam Angle 90 Degrees Trim colour White Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Shatterproof Mounting type Recessed LED source SMD Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty 12 Pallet Qty 384	Weight	0.5
Lumen output IP rating 44 CRI Beam Angle 90 Degrees Trim colour White Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Output current 600 mA Constant current/voltage Shatterproof Mounting type LED source Material Lamp Type Dimming Input voltage Diffuser Opal Wiring method Weatherproof Box Qty 12 Pallet Qty 384	Light Colour	3CCT
IP rating CRI 80 Beam Angle 90 Degrees Trim colour White Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Shatterproof Mounting type Recessed LED source SMD Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty 12 Pallet Qty 384	Wattage	18/20/23/25/28/30 W
CRI 80 Beam Angle 90 Degrees Trim colour White Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Shatterproof Mounting type Recessed LED source SMD Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty 12 Pallet Qty 384	Lumen output	2282, 2594, 2506 lm
Beam Angle 90 Degrees Trim colour White Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Shatterproof Mounting type Recessed LED source SMD Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty 12 Pallet Qty 384	IP rating	44
Trim colour Cut out 175-190 mm Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Output current 600 mA Constant current/voltage Shatterproof Mounting type LED source Material Lamp Type Dimming Input voltage Dimmable Aluminum LeD Diffuser Opal Wiring method Weatherproof Weatherproof Box Qty Pallet Qty SMD White 175-190 mm Constant Constant Current Constant Current Shatterproof Recessed LED source SMD Aluminum LED Dimming Iriac-Dimming Input voltage Veatherproof Weatherproof Box Qty 12 Pallet Qty 384	CRI	80
Cut out Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Mounting type Recessed LED source Material Lamp Type LED Dimming Input voltage Diffuser Opal Wiring method Weatherproof Weatherproof Weatherproof Weatherproof Weatherproof Weatherproof Weatherproof Weatherproof Weatherproof Box Qty Pallet Qty 384	Beam Angle	90 Degrees
Diameter 203 mm Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Shatterproof Mounting type Recessed LED source SMD Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty 12 Pallet Qty 384	Trim colour	White
Height 56 mm Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Shatterproof Mounting type Recessed LED source SMD Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty 12 Pallet Qty 384	Cut out	175-190 mm
Lifespan 50000 Hours Warranty 3 Years Dimmable Dimmable Output current 600 mA Constant Current Shatterproof Shatterproof Mounting type Recessed LED source SMD Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty 12 Pallet Qty 384	Diameter	203 mm
Warranty Dimmable Dimmable Output current 600 mA Constant current/voltage Shatterproof Mounting type LED source Material Lamp Type Dimming Input voltage Diffuser Wiring method Weatherproof Weatherproof Weatherproof Weatherproof Weatherproof Weatherproof Weatherproof Weatherproof Box Qty Pallet Qty Shatterproof Account Current Constant Current Shatterproof Recessed Aluminum LED Triac-Dimming Input voltage 200240V-AC Diffuser Weatherproof Weatherproof Weatherproof Weatherproof Box Qty 12 Pallet Qty Shatterproof Weatherproof Shatterproof Dimming Recessed Shatterproof Weatherproof Shatterproof Weatherproof Weatherproof Weatherproof Shatterproof Weatherproof Shatterproof Shatterproof Weatherproof Shatterproof Shatterproof Weatherproof Shatterproof Shatterproof Weatherproof Shatterproof S	Height	56 mm
Dimmable Output current 600 mA Constant current/voltage Shatterproof Mounting type LED source Material Lamp Type Dimming Input voltage Dimming Input voltage Diffuser Wiring method Weatherproof Dimmable Oon MA Constant Current Shatterproof Recessed LED Shatterproof Aluminum LED Triac-Dimming Input voltage Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty Pallet Qty 384	Lifespan	50000 Hours
Output current Constant current/voltage Shatterproof Mounting type LED source Material Lamp Type Dimming Input voltage Diffuser Wiring method Weatherproof Mounting type Recessed LED SMD Aluminum LED Triac-Dimming Input voltage Opal Wiring method Flex & Plug or Hardwire Weatherproof Box Qty Pallet Qty 384	Warranty	3 Years
Constant current/voltage Shatterproof Mounting type LED source Material Lamp Type Dimming Input voltage Diffuser Wiring method Weatherproof Box Qty Pallet Qty Constant Current Shatterproof Wecessed Aluminum LED Triac-Dimming Input voltage 200240V-AC Opal Weatherproof Weatherproof Weatherproof Box Qty 12	Dimmable	Dimmable
current/voltage Shatterproof Mounting type LED source Material Lamp Type Dimming Input voltage Diffuser Wiring method Weatherproof Weatherproof Box Qty Pallet Qty Constant Current Current Constant Current Current Constant Current Shatterproof Recessed LED Constant Current Constant Current Constant Current Constant Current Shatterproof Mounting type Recessed LED Constant Current Shatterproof Recessed LED Constant Current Shatterproof Recessed LED Constant Current Shatterproof Mounting type Constant Current Shatterproof Mounting type Constant Current Shatterproof Recessed LED Constant Current Shatterproof Mounting type Constant Current Shatterproof Shatterproof Figure Shatterproof Constant Current Shatterproof S	Output current	600 mA
Mounting type LED source SMD Material Lamp Type LED Dimming Input voltage Diffuser Wiring method Weatherproof Box Qty Pallet Qty SMD Aluminum LED Triac-Dimming 200240V-AC Opal Wiring method Flex & Plug or Hardwire Weatherproof 384		Constant Current
LED source Material Lamp Type LED Dimming Input voltage Diffuser Wiring method Weatherproof Box Qty Pallet Qty SMD Aluminum LED Triac-Dimming 200240V-AC Opal Flex & Plug or Hardwire Weatherproof Weatherproof 384	Shatterproof	Shatterproof
Material Aluminum Lamp Type LED Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Weatherproof Box Qty 12 Pallet Qty 384	Mounting type	Recessed
Lamp Type Dimming Input voltage Diffuser Opal Wiring method Weatherproof Box Qty Pallet Qty LED Triac-Dimming 200240V-AC Opal Flex & Plug or Hardwire Weatherproof 384	LED source	SMD
Dimming Triac-Dimming Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Weatherproof Box Qty 12 Pallet Qty 384	Material	Aluminum
Input voltage 200240V-AC Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Weatherproof Box Qty 12 Pallet Qty 384	Lamp Type	LED
Diffuser Opal Wiring method Flex & Plug or Hardwire Weatherproof Weatherproof Box Qty 12 Pallet Qty 384	Dimming	Triac-Dimming
Wiring method Flex & Plug or Hardwire Weatherproof Weatherproof Box Qty 12 Pallet Qty 384	Input voltage	200240V-AC
Weatherproof Box Qty 12 Pallet Qty 384	Diffuser	Opal
Box Qty 12 Pallet Qty 384	Wiring method	Flex & Plug or Hardwire
Pallet Qty 384	Weatherproof	Weatherproof
	Box Qty	12
Kelvin 3000K/4000K/5700K		384
	Kelvin	3000K/4000K/5700K



Dimensional Drawings



Photometric information available upon request.