



## LED DOWNLIGHT 3K/4K CCT MUST ADD DRIVER 14W/20W/30W

### VBLDL-446A-1-CCT



Equipped with OSRAM LED chips, flexible driver options and a unique heat sink for maximum heat dissipation. These recessed downlights are compatible with most trailing edge dimming systems. This fitting requires a compatible driver to run. Depending on the driver chosen the wattage will become 14W, 20W or 28W. Compatible drivers can be found under the code VBLDL-446. Features a 35,000 hour lifespan & 3 year warranty.

### Features & Benefits

- Choose your cutout and then choose your wattage
- Change the colour temperature with the flick of a switch - CCT can be switched by the slide button on the back of the fitting
- Unique heat-sink design for excellent heat dissipation
- Deep recessed low glare design
- Flexible driver options-3 wattages to choose from
- Dimmable with most trailing edge dimmers
- 35,000 hour lifespan
- Environmentally friendly
- 3 year warranty



# LED DOWNLIGHT 3K/4K CCT MUST ADD DRIVER 14W/20W/30W

VBLDL-446A-1-CCT

## Specifications

<b>SKU</b>	VBLDL-446A-1-CCT
<b>Luminaire efficacy</b>	105 lm/W
<b>EAN</b>	9340994022314
<b>Light Colour</b>	CCT
<b>Wattage</b>	20 W
<b>Lumen output</b>	2100 lm
<b>IP rating</b>	54
<b>CRI</b>	90
<b>Beam Angle</b>	85 Degrees
<b>Trim colour</b>	White
<b>Cut out</b>	200 mm
<b>Diameter</b>	230 mm
<b>Lifespan</b>	35000 Hours
<b>Warranty</b>	3 Years
<b>Constant current/voltage</b>	Constant Current
<b>Mounting type</b>	Recessed
<b>LED source</b>	Osram Olson
<b>Material</b>	Thermo Plastic
<b>Lamp Type</b>	LED
<b>Dimming</b>	Triac Dimming
<b>Input voltage</b>	220V-240V AC 50HZ
<b>Wiring method</b>	Flex & Plug
<b>Weatherproof</b>	Weatherproof
<b>Working temperature</b>	-20°C ~ 45°C



Photometric information available upon request.