



## 54W LED RGB FLOODLIGHT WITH REMOTE

### VBLFL-54W-4-RGB



The VIBE LED RGB Floodlight delivers bright, energy-efficient lighting with vibrant colour options. Built tough for outdoor use (IP65), it features a tempered glass lens, anti-condensation breather valve, and durable SMALITE LEDs. Choose from multiple colours using the remote. Easy to install with 1.5m flex and plug. 50,000-hour lifespan. 3-year warranty.

### Features & Benefits

- Advanced input under/over voltage protection for improved reliability
- Equipped with SMALITE high voltage LED chips
- 4mm tempered glass, high light transmittance
- Breather valve allows to adjust the floodlights capacity pressure to avoid the formation of water vapour inside the fitting
- Colour selectable via remote
- Equipped with energy efficient 3 in 1 RGB chips
- Comes complete with 1.5M flex & plug
- IP65 rated
- 50,000 hour lifespan
- 3 year warranty



## 54W LED RGB FLOODLIGHT WITH REMOTE


VBLFL-54W-4-RGB

### Specifications

SKU	VBLFL-54W-4-RGB
Luminaire efficacy	32 lm/W
EAN	9340994031804
Light Colour	RGB
Wattage	54 W
Lumen output	1728 lm
IP rating	65
Beam Angle	110 Degrees
Trim colour	Black
Length	160 mm
Width	27 mm
Height	125 mm
Lifespan	50000 Hours
Warranty	3 Years
Mounting type	Surface
Material	Powder coated die-cast aluminium
Accessories	Remote & bracket included
Lamp Type	LED
Input voltage	240 Volt AC 50HZ
Wiring method	Flex & Plug or Hardwire
Working temperature	-20°C ~ 45°C



### Dimensional Drawings



Photometric information available upon request.

Remote Control Guide – RGB Floodlight

ON/OFF: Power the light on or off.

▲ / ▼: Adjust brightness.

R / G / B / W: Select Red, Green, Blue, or White light.

Color Buttons: Choose from 16 preset colors instantly.

FLASH: Fast color jump.

STROBE: Slow flashing.

FADE: Gradual transition between colors.

SMOOTH: Soft, steady color change cycle.

#### Usage Tips

Aim the remote directly at the floodlight for best performance.

Ensure there are no obstructions between the remote and the receiver.

The remote operates using infrared (IR); range is approximately 5-10 meters.