



## VBLFL-RGB-SERIES

### RGB LED FLOODLIGHTS

The VBLFL-RGB Series are our lightweight, patented outdoor LED floodlight, perfect for event, landscape, and architectural lighting. These powerful lights feature a 3-in-1 RGB chip and a high electroplated reflector, delivering uniform, soft, and vivid colours that create vibrant atmospheres and stunning visual effects. With an easy-to-use remote, you can quickly change colours, make the lights fade smoothly, or flash in patterns to highlight areas or create a mood.

Built with a robust, weather-resistant housing, the RGB Series is ideal for both indoor and outdoor applications. Long-lasting LEDs ensure high output and energy efficiency, while the slimline design allows for discreet yet impactful installation. Perfect for building facades, stages, signage or feature walls.

#### KEY FEATURES

- 3-in-1 RGB chip with a high-efficiency reflector to give a soft uniform light distribution
- Powder-coated die-cast aluminium construction with tempered clear glass diffuser
- Complete with a remote control to allow the user to achieve various colour options
- Comes complete with 1.5M flex & plug
- IP65 rated
- 50,000-hour lifespan
- 3-year warranty



## SPECIFICATIONS

|                   |                  |                  |
|-------------------|------------------|------------------|
| SKU               | VBLFL-96W-4-RGB  | VBLFL-54W-4-RGB  |
| Power (W)         | 96               | 54               |
| Lumens (LM)       | 3072             | 1728             |
| Input Voltage (V) | 240 Volt AC 50HZ | 240 Volt AC 50HZ |
| Colour Temp       | RGB              | RGB              |
| Beam Angle        | 110              | 110              |
| IP Rating         | 65               | 65               |
| Trim Colour       | Black            | Black            |
| Weatherproof      | Yes              | Yes              |
| Mounting Type     | Surface          | Surface          |
| Height (MM)       | 165              | 125              |
| Width (MM)        | 30               | 27               |
| Length (MM)       | 220              | 160              |
| Lifespan (HRS)    | 50000            | 50000            |
| Warranty (YRS)    | 3                | 3                |

## DIMENSIONAL DRAWINGS

