



## T8 3FT 16W LED TUBE 6500K FROSTED 150LM/W

### VBLFT-335-F-65



Vibe LED Tubes are a direct replacement for existing T8 Fluorescent tubes, they are environmentally friendly (do not contain harmful substances) and have a high quality aluminium body with excellent heat dissipation.

### Features & Benefits

- High quality aluminium body with excellent heat dissipation
- Direct replacement for T8 fluorescent Lamps
- Comes with frosted PC cover & rotatable end caps
- Equipped saving potential up to 60%
- Equipped with high power EPISTAR SMD LED chips
- Environmentally friendly
- 50,000 hour lifespan
- 5 year warranty

# T8 3FT 16W LED TUBE 6500K FROSTED 150LM/W


**VBLFT-335-F-65**

## Specifications

|                            |                     |
|----------------------------|---------------------|
| <b>SKU</b>                 | VBLFT-335-F-65      |
| <b>Luminaire efficacy</b>  | 153 lm/W            |
| <b>EAN</b>                 | 9340994409917       |
| <b>Light Colour</b>        | Daylight            |
| <b>Wattage</b>             | 16 W                |
| <b>Lumen output</b>        | 2448 lm             |
| <b>IP rating</b>           | 20                  |
| <b>CRI</b>                 | 80                  |
| <b>Beam Angle</b>          | 120 Degrees         |
| <b>Base Type</b>           | G13                 |
| <b>Diameter</b>            | 26 mm               |
| <b>Length</b>              | 894 mm              |
| <b>Lifespan</b>            | 50000 Hours         |
| <b>Warranty</b>            | 5 Years             |
| <b>Dimmable</b>            | Non-Dimmable        |
| <b>Shatterproof</b>        | Shatterproof        |
| <b>LED source</b>          | Epistar             |
| <b>Lamp Type</b>           | LED                 |
| <b>Input voltage</b>       | 85V-265V AC 50-60HZ |
| <b>Diffuser</b>            | Frosted             |
| <b>Weatherproof</b>        | Non-weatherproof    |
| <b>Working temperature</b> | -20° ~ 45°C         |
| <b>Box Qty</b>             | 25                  |
| <b>Kelvin</b>              | 6500K               |



## Dimensional Drawings



*Photometric information available upon request.*