



## T8 3FT 12W LED TUBE PINK OPAL

### VBLFT-335-F-P



Featuring a high quality aluminium body, choice of clear or frosted cover, unique rotatable end cap and an energy saving of up to 60% the LED Tube Lamps make great direct replacements for T8 fluorescent lamps. Enhances the display of meat products.

### Features & Benefits

- High quality aluminium body with excellent heat dissipation
- Direct replacement for T8 fluorescent Lamps
- Comes with frosted PC cover & rotatable end caps
- Equipped saving potential up to 60%
- Equipped with high power EPISTAR SMD LED chips
- Environmentally friendly
- 50,000 hour lifespan
- 5 year warranty

# T8 3FT 12W LED TUBE PINK OPAL


VBLFT-335-F-P

## Specifications

|                            |                                    |
|----------------------------|------------------------------------|
| <b>SKU</b>                 | VBLFT-335-F-P                      |
| <b>Luminaire efficacy</b>  | 60 lm/W                            |
| <b>EAN</b>                 | 9340994402345                      |
| <b>Weight</b>              | 0.5                                |
| <b>Light Colour</b>        | Pink                               |
| <b>Wattage</b>             | 12 W                               |
| <b>Lumen output</b>        | 720 lm                             |
| <b>CRI</b>                 | 80                                 |
| <b>Beam Angle</b>          | 120 Degrees                        |
| <b>Base Type</b>           | G13                                |
| <b>Diameter</b>            | 29 mm                              |
| <b>Length</b>              | 894 mm                             |
| <b>Lifespan</b>            | 50000 Hours                        |
| <b>Warranty</b>            | 5 Years                            |
| <b>Dimmable</b>            | Non-Dimmable                       |
| <b>LED source</b>          | Epistar                            |
| <b>Material</b>            | Aluminium Alloy & PC Frosted Cover |
| <b>Lamp Type</b>           | LED                                |
| <b>Input voltage</b>       | 85V-265V AC 50-60HZ                |
| <b>Diffuser</b>            | Opal                               |
| <b>Working temperature</b> | -20°C ~ 40°C                       |
| <b>Box Qty</b>             | 25                                 |



## Dimensional Drawings



Photometric information available upon request.