



105 Series

VBLPD-105-4-3K



These stunning, architecturally designed, Black, 3K, 105 Series Barrel LED Pendant Lights make a striking feature light in any home, office, gallery, museum or retail store. Equipped with Sharp COB LED Chips, the 3000K provides a 1100 lumen output and 50° beam. Available in 4K, 3K, Black or white, they are sure to be a feature light in any space. Includes 40,000 hour lifespan and 5 year warranty.

Features & Benefits

- Architecturally designed LED Pendant
- Equipped with SHARP COB LED chips
- Low glare lighting
- Available in White and Black trim colour
- 40,000 hour lifespan
- 5 year warranty
- 50,000 hour lifespan
- 3 year warranty



105 Series

Specifications

SKUVBLPD-105-4-3KLuminaire efficacy85 lm/WEAN9340994402390Light ColourWarm WhiteWattage13 WWattage13 WLumen output100 lmIP rating20CRI80Beam Angle50 DegreesTrim colourBlackDiameter60 mmHeight300 mmKarranty5 YearsVarrantySigendedMounting typeSiapendedLED sourceAnarpImpative20V-265V AC 50hzWeatherproof1000 KWorking temperature20°C ~ 45°CKelvin3000K		
EAN9340994402390Light ColourWarm WhiteWattage13 WWattage13 WLumen output100 ImIP rating20CRI80Beam Angle50 DegreesDiameter60 mmDiameter300 MmHeight300 MmIffespan91 YearsMounting typeSinspendedIED sourceSinspendedMaterialAluminiumLamp TypeEDImput voltage92 YearsWeatherproofCalor Jean Jean Jean Jean Jean Jean Jean Jean	SKU	VBLPD-105-4-3K
Light ColourWarm WhiteLight ColourWarm WhiteWattage13 WLumen output1100 lmIP rating20CRI80Beam Angle50 DegreesTrim colourBlackDiameter60 mmHeight300 mmLifespan40000 HoursWarranty5 YearsDimmableNon-DimmableMounting typeSuspendedLED sourceSharpMaterial220V-265V AC 50hzInput voltage-20°C ~ 45°C	Luminaire efficacy	85 lm/W
NameWattage13 WLumen output1100 lmIP rating20CRI80Beam Angle50 DegreesTrim colourBlackDiameter60 mmHeight300 mmLifespan40000 HoursWarranty5 YearsDimmableNon-DimmableMounting typeSuspendedLED sourceSharpMaterial220V-265V AC 50hzInput voltageindoor Use OnlyWeatherproofindoor Use Only	EAN	9340994402390
Lumen outputII 00 lmIP rating20IP rating20CRI80Beam Angle50 DegreesTrim colourBlackDiameter60 mmDiameter300 mmHeight300 nmLifespan40000 HoursWarranty5 YearsDimmableNon-DimmableIED sourceSharpMaterial20V-265V AC 50hzInput voltage20V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature20°C ~ 45°C	Light Colour	Warm White
IncominationIP rating20CRI80Beam Angle50 DegreesTrim colourBlackDiameter60 mmHeight300 mmIfespan40000 HoursWarranty5 YearsDimmableNon-DimmableIED sourceSharpMaterialAluminiumImput voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature220°C ~ 45°C	Wattage	13 W
CRI80Beam Angle50 DegreesTrim colourBlackDiameter60 mmDiameter300 mmHeight300 mmKifespan40000 HoursWarranty5 YearsDimmableNon-DimmableMounting typeSuspendedKaterialAluminiumLED sourceSharpInput voltage20V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature20°C ~ 45°C	Lumen output	1100 lm
Beam Angle50 DegreesBeam Angle50 DegreesTrim colourBlackDiameter60 mmDiameter300 mmHeight300 mmLifespan40000 HoursWarranty5 YearsDimmableNon-DimmableMounting typeSuspendedLED sourceSharpMaterial20V-265V AC 50hzInput voltageIndoor Use OnlyWeatherproof-20°C ~ 45°C	IP rating	20
Trim colourBlackDiameter60 mmDiameter300 mmHeight300 mmLifespan4000 HoursWarranty5 YearsDimmableNon-DimmableMounting typeSuspendedLED sourceSharpMaterialLEDJumniumEDInput voltageIndoor Use OnlyWeatherproof-20°C ~ 45°C	CRI	80
Diameter60 mmHeight300 mmLifespan40000 HoursWarranty5 YearsDimmableNon-DimmableMounting typeSuspendedLED sourceSharpMaterialAluminiumLamp TypeLEDInput voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Beam Angle	50 Degrees
HeightStormHeight300 mmLifespan40000 HoursWarranty5 YearsDimmableNon-DimmableMounting typeSuspendedLED sourceSharpMaterialAluminiumLamp TypeLEDInput voltageSource onlyWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Trim colour	Black
Lifespan40000 HoursWarranty5 YearsDimmableNon-DimmableMounting typeSuspendedLED sourceSharpMaterialAluminiumLamp TypeLEDInput voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Diameter	60 mm
Warranty5 YearsDimmableNon-DimmableMounting typeSuspendedLED sourceSharpMaterialAluminiumLamp TypeLEDInput voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Height	300 mm
DimmableNon-DimmableMounting typeSuspendedLED sourceSharpMaterialAluminiumLamp TypeLEDInput voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Lifespan	40000 Hours
Mounting typeSuspendedLED sourceSharpMaterialAluminiumLamp TypeLEDInput voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Warranty	5 Years
LED sourceSharpMaterialAluminiumLamp TypeLEDInput voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Dimmable	Non-Dimmable
MaterialAluminiumLamp TypeLEDInput voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Mounting type	Suspended
Lamp TypeLEDInput voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	LED source	Sharp
Input voltage220V-265V AC 50hzWeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Material	Aluminium
WeatherproofIndoor Use OnlyWorking temperature-20°C ~ 45°C	Lamp Type	LED
Working temperature-20°C ~ 45°C	Input voltage	220V-265V AC 50hz
S Provide S Prov	Weatherproof	Indoor Use Only
Kelvin 3000K	Working temperature	-20°C ~ 45°C
	Kelvin	3000K

Photometric information available upon request.



Dimensional Drawings

