



# 410 Series

#### VBLSL-410-4-30W-50



Our VIBE 30W, 5000K LED Street Lights are manufactured with a die-cast aluminium. With a sleek, modern design, and adjustable  $\pm$  15° pole arm, these fittings are easy to clean and maintain. They are supplied with an IP65 weather rating, IK08 impact resistance, 50,000 hour lifespan and 5 year warranty. Emitting a large 3,600 lumens per fitting, they are great for council streets, paths, tracks and carparks. Please Note: All VIBE LED Street Lights are recommended to be mounted securely to a plinth/concrete base and not covered by any organic materials (dirt/mulch/sand ect) to avoid condensation entering and subsequently corroding the fitting. Not following this installation recommendation will void any stated warranty.

### **Features & Benefits**

- Die-casting aluminium heat sink
- Adjustable pole arm  $\pm$  15°
- •Easy to maintain
- 10KV surge protection
- IP65 & IK08 rated
- 50,000 hour lifespan
- 5 year warranty

## 410 Series

### Specifications

Luminaire efficacy120 lm/WEAN9340994027432Weight3Light ColourNatural WhiteWattage30 WLumen output3600 lmIP rating65IK Rating8CRI80Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWeatherproofWeatherproof		
EAN9340994027432Weight3Light ColourNatural WhiteWattage30 WLumen output3600 lmIP rating65IK Rating8CRI80Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWeatherproofWeatherproof	SKU	VBLSL-410-4-30W-50
Weight3Light ColourNatural WhiteWattage30 WLumen output3600 ImIk mating65IK Rating8CRI80Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWeatherproofWeatherproof	Luminaire efficacy	120 lm/W
Light ColourNatural WhiteWattage30 WLumen output3600 lmIP rating65IK Rating8CRI80Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursKatranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWeatherproofWeatherproof	EAN	9340994027432
Wattage30 WLumen output3600 lmIP rating65IK Rating8CRI80Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDLamp TypeLEDInput voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	Weight	3
Lumen output3600 lmIP rating65IK Rating8CRI80Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWeatherproofWeatherproof	Light Colour	Natural White
IP rating65IK Rating8CRI80Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWeatherproofWeatherproof	Wattage	30 W
IK Rating8IK Rating8CRI80Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWeatherproofWeatherproof	Lumen output	3600 lm
CRI80Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWeatherproofWeatherproof	IP rating	65
Trim colourBlackLength610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWeatherproofWeatherproof	IK Rating	8
Length610 mmWidth240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	CRI	80
Width240 mmHeight130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	Trim colour	Black
Height130 mmLifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	Length	610 mm
Lifespan50000 HoursWarranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	Width	240 mm
Warranty5 YearsLED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	Height	130 mm
LED sourceSMDMaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	Lifespan	50000 Hours
MaterialDie Cast AluminumLamp TypeLEDInput voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	Warranty	5 Years
Lamp TypeLEDInput voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	LED source	SMD
Input voltage220V-240V AC 50HZWiring methodHardwireWeatherproofWeatherproof	Material	Die Cast Aluminum
Wiring methodHardwireWeatherproofWeatherproof	Lamp Type	LED
Weatherproof Weatherproof	Input voltage	220V-240V AC 50HZ
	Wiring method	Hardwire
Working temperature -20 to 45 degrees	Weatherproof	Weatherproof
	Working temperature	-20 to 45 degrees
<b>Kelvin</b> 5000K	Kelvin	5000K



Photometric information available upon request.