



50W 5K LED STREET LIGHT c/w SLIP FITTER 10KV SURGE (D)

VBLSL-410-4-50W-50



Our VIBE 50W, 5000K LED Street Lights are manufactured with a die-cast aluminium. With a sleek, modern design, and adjustable \pm 15° pole arm, these fittings are easy to clean and maintain. They are supplied with an IP65 weather rating, IK08 impact resistance, 50,000 hour lifespan and 5 year warranty. Emitting a large 6,000 lumens per fitting, they are great for council streets, paths, tracks and carparks. Please Note: All VIBE LED Street Lights are recommended to be mounted securely to a plinth/concrete base and not covered by any organic materials (dirt/mulch/sand ect) to avoid condensation entering and subsequently corroding the fitting. Not following this installation recommendation will void any stated warranty.

Features & Benefits

- Die-casting aluminium heat sink
- Adjustable pole arm $\pm~15^\circ$
- •Easy to maintain
- 10KV surge protection
- IP65 & IK08 rated
- 50,000 hour lifespan
- 5 year warranty

50W 5K LED STREET LIGHT c/w SLIP FITTER 10KV SURGE (D)

VBLSL-410-4-50W-50

Specifications

| SKU | VBLSL-410-4-50W-50 |
|---------------------|--------------------|
| Luminaire efficacy | 120 lm/W |
| EAN | 9340994027449 |
| Light Colour | Natural White |
| Wattage | 50 W |
| Lumen output | 6000 lm |
| IP rating | 65 |
| IK Rating | 8 |
| CRI | 80 |
| Trim colour | Black |
| Length | 233 mm |
| Width | 435 mm |
| Lifespan | 50000 Hours |
| Warranty | 5 Years |
| LED source | SMD |
| Material | Die Cast Aluminum |
| Lamp Type | LED |
| Input voltage | 220V-240V AC 50HZ |
| Wiring method | Hardwire |
| Weatherproof | Weatherproof |
| Working temperature | -20 to 45 degrees |
| Kelvin | 5000K |
| | |

Photometric information available upon request.



www.anllighting.com.au