



## LED STREET LIGHT 150W

### **VBLSL-430-4-150W-50Z**



Introducing our VIBE 150W LED Street Lights, purpose-built to excel in Australian conditions. Made from robust die-cast aluminum, they seamlessly blend a contemporary aesthetic with practical functionality. The adjustable  $\pm 10^\circ$  pole arm can be mounted either horizontally or vertically, ensuring versatile installation options. Tailoring the illumination to your specific requirements is effortless, thanks to the adjustable settings of 150W, 120W, 90W, or 60W. What truly sets these lights apart is their robust 20kv surge protection, offering a safeguard against electrical surges. With a remarkable 50,000-hour lifespan and an impressive 150 lm/w luminous efficacy, they are the ultimate choice for illuminating streets, pathways, tracks, and car parks. Plus, they come backed by a generous 5-year warranty, providing you with peace of mind and reliability you can trust. An optional ZHAGA Daylight sensor is available for intelligent lighting control.

### **Features & Benefits**

- Die-casting aluminium heat sink
- Adjustable pole arm  $\pm 10^\circ$
- 4 Wattage adjustable 150/120/90/60W
- Easy to maintain
- 20KV surge protection
- IP65 & IK08 rated
- 50,000 hour lifespan
- 5 year warranty

# LED STREET LIGHT 150W

VBLSL-430-4-150W-50Z

## Specifications

<b>SKU</b>	VBLSL-430-4-150W-50Z
<b>Luminaire efficacy</b>	150 lm/W
<b>EAN</b>	9340994030319
<b>Weight</b>	4.2
<b>Light Colour</b>	Natural White
<b>Wattage</b>	150/120/90/60 W
<b>Lumen output</b>	22500/18000/13500/9000 lm
<b>IP rating</b>	65
<b>IK Rating</b>	8
<b>CRI</b>	80
<b>Beam Angle</b>	TYPE III Degrees
<b>Trim colour</b>	Black
<b>Length</b>	710 mm
<b>Width</b>	265 mm
<b>Height</b>	108 mm
<b>Lifespan</b>	50000 Hours
<b>Warranty</b>	5 Years
<b>Dimmable</b>	Dimmable
<b>LED source</b>	SMD
<b>Material</b>	Die Cast Aluminum
<b>Accessories</b>	ZHAGA DAYLIGHT SENSOR
<b>Lamp Type</b>	LED
<b>Dimming</b>	0-10V
<b>Input voltage</b>	220V-240V AC 50HZ
<b>Wiring method</b>	Hardwire
<b>Weatherproof</b>	Weatherproof
<b>Working temperature</b>	-20 to 45 degrees
<b>Kelvin</b>	5000K
<b>Power Adjustable</b>	Yes

Photometric information available upon request.

Built in spirit level

Recommended pole spigot size: 60mm diameter

Optional Zhaga daylight sensor available



Dimensional Drawings

