



LED STRIP 9.6W/M 24VDC 6K IP20 CRI90+ 5MT 140LED/M

VBLST-096NW-20



Our 9.6W/m, 24V, Daylight, IP20 LED Strip lighting is a popular, versatile light source that will assist in creating inspiring lighting solutions. Due to being relatively inexpensive, easy to install and extremely flexible - LED strip lights are an ideal choice to enhance the mood in modern or contemporary architecture. The VIBE Range offers a huge variety of LED strip lights to choose from in different lengths, colours, and IP Ratings - with a host of accessories and aluminium extrusions to bring your design to life. Ask your VIBE Reseller about custom cut and assembly options for faster, easier installation on-site.

Features & Benefits

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20 rated
- 3M adhesive taper
- 120° beam angle
- 50,000 hours lifespan
- 3 years warranty ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



Specifications

Luminaire efficacy EAN 9340994023250 Light Colour Wattage Lumen output IP rating CRI Beam Angle Cut out VBLST-096NW-20 124 lm/W 9340994023250 Natural White 1197 lm 120
EAN 9340994023250 Light Colour Natural White Wattage 9.6 W Lumen output 1197 lm IP rating 20 CRI 90 Beam Angle 120 Degrees Cut out 50mm Cutting Intervals, Spaced 7.14mm mm
Light Colour Wattage 9.6 W Lumen output 1197 Im IP rating CRI 90 Beam Angle 120 Degrees Cut out Natural White 9.6 W 1197 Im
Wattage 9.6 W Lumen output 1197 lm IP rating 20 CRI 90 Beam Angle 120 Degrees Cut out 50mm Cutting Intervals, Spaced 7.14mm mm
Lumen output IP rating CRI Beam Angle Cut out 1197 lm 20 90 120 Degrees 50mm Cutting Intervals, Spaced 7.14mm mm
IP rating 20 CRI 90 Beam Angle 120 Degrees Cut out 50mm Cutting Intervals, Spaced 7.14mm mm
CRI 90 Beam Angle 120 Degrees Cut out 50mm Cutting Intervals, Spaced 7.14mm mm
Beam Angle 120 Degrees Cut out 50mm Cutting Intervals, Spaced 7.14mm mm
Cut out 50mm Cutting Intervals, Spaced 7.14mm mm
7.14mm mm
Lifeanan F0000 Hours
Lifespan 50000 Hours
Warranty 3 Years
Constant current/voltage Constant Voltage
LED source SMD
Accessories VBLST-CTRL-BOX and VBLST-CTRL-DIM
Lamp Type LED
Dimming PWM
Input voltage 24 Volt DC
Wiring method Fly Leads
Weatherproof Non-weatherproof
Working temperature -20°C ~ 45°C
Kelvin 5000K



Photometric information available upon request.