



LED STRIP 14.4W/M 24V 3000K CRI90+ IP20 1MT

VBLST-144WW-20



Our 14.4W/m, 24V, 4000K, IP54, CRI90+ LED Strip lighting is a popular, versatile light source that will assist in creating inspiring lighting solutions. Due to being relatively inexpensive, easy to install and extremely flexible - LED strip lights are an ideal choice to enhance the mood in modern or contemporary architecture. The VIBE Range offers a huge variety of LED strip lights to choose from in different lengths, colours, and IP Ratings - with a host of accessories and aluminium extrusions to bring your design to life. Ask your VIBE Reseller about custom cut and assembly options for faster, easier installation on-site.

Features & Benefits

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20/IP54 rated
- 3M adhesive taper
- 120° Beam angle
- 50,000 hours lifespan
- 3 years warranty - ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



LED STRIP 14.4W/M 24V 3000K CRI90+ IP20 1MT

VBLST-144WW-20

Specifications

| | |
|---------------------------------|--|
| SKU | VBLST-144WW-20 |
| Luminaire efficacy | 109 lm/W |
| EAN | 9340994023625 |
| Light Colour | Warm White |
| Wattage | 14.4 W |
| Lumen output | 1575 lm |
| IP rating | 20 |
| CRI | 90 |
| Beam Angle | 120 Degrees |
| Cut out | 50mm Cutting Intervals, Spaced 7.14mm mm |
| Length | 1000 mm |
| Lifespan | 50000 Hours |
| Warranty | 3 Years |
| Constant current/voltage | Constant Voltage |
| LED source | SMD |
| Accessories | VBLST-CTRL-BOX and VBLST-CTRL-DIM |
| Lamp Type | LED |
| Dimming | PWM |
| Input voltage | 24 Volt DC |
| Wiring method | Fly Leads |
| Working temperature | -20°C ~ 45°C |
| Kelvin | 3000K |



Photometric information available upon request.