



## 12W LED UPLIGHT IP67 24V 3K 50DEG REF 316 S/S

### VBLUP-216-24V-3K



Our 12W, 4000K, 24V LED In-ground Uplights are a fantastic in-ground path lighting option. With an IP67 rating and IK10 rating, they are ideal in outdoor areas They can withstand 20KN of static force allowing them to be driven over. With an adjustable internal lens, they can be adapted to meet individual lighting desires to create symmetrical or asymmetrical beam spread. Includes a 50,000 hour lifespan and 5 year warranty.

### **Features & Benefits**

+ 24V & 240V in-ground Uplight with 316 Stainless Steel face and die-cast body

- Equipped with CITIZEN LED chips
- Adjustable internal lens to create symmetrical or asymmetrical beam spread
- Can be fitted with a range of accessories including
- reflectors, honeycomb lenses and diffuser glasses
- IP67 rated
- $\bullet\,$  IK10 able to withstand up to 20 KN of static force (able to be driven over)
- 50,000 hour lifespan
- 5 year warranty


# 12W LED UPLIGHT IP67 24V 3K 50DEG REF 316 S/S

### VBLUP-216-24V-3K

### Specifications

Luminaire efficacy109 lm/WEAN9340994016597Light ColourWarm WhiteWattage12 WLumen output1317 lmIP rating67IK Rating10CRI80Beam Angle50 DegreesTrim colourStainless 316Diameter100 mmWidth180 mmHeight190 mmIffespan50000 HoursWarranty5 YearsDiameterShatterproofShatterproofShatterproofMaterial316 Stainless steel front and die ast bodyAccessoriesLEDLump TypeLEDLump TypeKardwireKatherproofStainless steel front and die ast bodyKatherproofHEDKaterprofHEDKaterprofMaterialMaterial100 foursKaterprofStainless steel front and die ast bodyKaterprofKaterproofKaterprofMaterproofKaterprofKaterproofKaterprofKaterproofKaterprofKaterproofKaterprofKaterproofKaterprof </th <th>SKU</th> <th>VBLUP-216-24V-3K</th>	SKU	VBLUP-216-24V-3K
Light ColourWarm WhiteWattage12 WWattage1317 ImLumen output67IP rating67IK Rating10CRI80Beam Angle50 DegreesTrim colourStainless 316Diameter175 mmLength100 mmWidth180 mmHeight190 mmLifespan5000 HoursWarranty5 YearsDinmableNon-DimmableShatterproofShatterproofMaterial316 Stainless steel front and die ast bodyAccessoriesLEDLimp TypeLEDInput voltage24 Volt DCWiring methodHardwire	Luminaire efficacy	109 lm/W
Wattage12 WLumen output1317 lmIP rating67IK Rating10IK Rating50 DegreesCRI80Beam Angle50 DegreesTrim colourStainless 316Diameter100 mmUddth180 mmHeight190 mmLifespanSo000 HoursWarranty5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenAccessoriesQptional beam angles & Accessories availableLEDLEDInput voltageKardwire	EAN	9340994016597
Lumen output1317 lmIP rating67IR Rating10IK Rating50 DegreesCRI80Beam Angle50 DegreesTrim colourStainless 316Diameter100 mmLength100 mmWidth180 mmHeight190 mmLifespan5 YearsDimmableShatterproofShatterproofShatterproofMounting typeRecessedLED sourceCitizenAccessoriesOptional beam angles & Accessories availableLamp TypeLEDInput voltageKardwire	Light Colour	Warm White
IP rating67IK Rating10CRI80Beam Angle50 DegreesTrim colourStainless 316Diameter175 mmLength100 mmWidth180 mmHeight190 mmLifespanSoudo HoursWarranty5 YearsDimmableShatterproofShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die- cast bodyAccessoriesOptional beam angles & Accessories availableIpput voltage24 Volt DCWiring methodHardwire	Wattage	12 W
IK Rating10IK Rating10CRI80Beam Angle50 DegreesTrim colourStainless 316Diameter175 mmLength100 mmWidth180 mmHeight190 mmLifespan5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and diecast bodyAccessoriesOptional beam angles & Accessories availableImput voltage24 Volt DCWiring methodHardwire	Lumen output	1317 lm
CRI80Beam Angle50 DegreesTrim colourStainless 316Diameter175 mmLength100 mmWidth180 mmHeight190 mmLifespan5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die- cast bodyLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	IP rating	67
Beam Angle50 DegreesTrim colourStainless 316Diameter175 mmLength100 mmWidth180 mmHeight190 mmLifespanSolood HoursWarranty5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die- cast bodyLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	IK Rating	10
Trim colourStainless 316Diameter175 mmLength100 mmWidth180 mmHeight190 mmLifespan50000 HoursWarranty5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die- cast bodyLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	CRI	80
Diameter175 mmLength100 mmWidth180 mmHeight190 mmLifespan50000 HoursWarranty5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die- cast bodyLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	Beam Angle	50 Degrees
Length100 mmWidth180 mmHeight190 mmLifespan50000 HoursWarranty5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and diecast bodyAccessoriesOptional beam angles & Accessories availableLEDLEDInput voltage24 Volt DCWiring methodHardwire	Trim colour	Stainless 316
Width180 mmHeight190 mmLifespan50000 HoursWarranty5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die- cast bodyAccessoriesOptional beam angles & Accessories availableLED1EDInput voltage24 Volt DCWiring methodHardwire	Diameter	175 mm
Height190 mmLifespan50000 HoursWarranty5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die- cast bodyAccessoriesOptional beam angles & Accessories availableLEDLEDInput voltage24 Volt DCWiring methodHardwire	Length	100 mm
Lifespan50000 HoursWarranty5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and diecast bodyAccessoriesOptional beam angles & Accessories availableLEDLEDInput voltage24 Volt DCWiring methodHardwire	Width	180 mm
Warranty5 YearsDimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die- cast bodyAccessoriesOptional beam angles & Accessories availableLEDLEDInput voltage24 Volt DCWiring methodHardwire	Height	190 mm
DimmableNon-DimmableShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die- cast bodyAccessoriesOptional beam angles & Accessories availableLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	Lifespan	50000 Hours
ShatterproofShatterproofMounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and diecast bodyAccessoriesOptional beam angles & Accessories availableLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	Warranty	5 Years
Mounting typeRecessedLED sourceCitizenMaterial316 Stainless steel front and die cast bodyAccessoriesOptional beam angles & Accessories availableLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	Dimmable	Non-Dimmable
LED sourceCitizenMaterial316 Stainless steel front and diecast bodyAccessoriesOptional beam angles & Accessories availableLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	Shatterproof	Shatterproof
Material316 Stainless steel front and die- cast bodyAccessoriesOptional beam angles & Accessories availableLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	Mounting type	Recessed
Materialcast bodyAccessoriesOptional beam angles & Accessories availableLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	LED source	Citizen
AccessoriesAccessories availableLamp TypeLEDInput voltage24 Volt DCWiring methodHardwire	Material	
Input voltage 24 Volt DC   Wiring method Hardwire	Accessories	
Wiring method Hardwire	Lamp Type	LED
-	Input voltage	24 Volt DC
Weatherproof Weatherproof	Wiring method	Hardwire
	Weatherproof	Weatherproof
<b>Working temperature</b> -20°C ~ 45°C	Working temperature	-20°C ~ 45°C
<b>Kelvin</b> 3000K	Kelvin	3000K

#### **Dimensional Drawings**



Photometric information available upon request.