



15W LED OVAL BUNKER BLACK TRIM 3CCT 1200-1250LM

VBLWL-212-4-CCT



VIBE's 15W LED Oval Bunker light is a great undercover outdoor wall light option with an IP54 weather rating. With a toughened moulded plastic body, frosted PC diffuser, and 120° beam angle, these lights will fit great in undercover walkways, gardens or as an exterior fitting for commercial buildings. Includes a 50,000 hour lifespan and 3 year warranty. Eyelid attachment available.

Features & Benefits

- Toughened moulded plastic body
- Frosted PC diffuser
- Equipped with EPISTAR LED chips
- 120° wide light beam angle
- IP54 rated for outdoor use
- 25,000 hour lifespan
- 3 year warranty

15W LED OVAL BUNKER BLACK TRIM 3CCT 1200-1250LM

VBLWL-212-4-CCT

Specifications

SKUVBLWL-212-4-CCTLuminaire efficacy84 lm/WEAN9340994020419Light Colour3CCTWattage15 WLumen output1260 lmIP rating54CRI80Beam Angle120 DegreesTrim colourBlackLength230 mmHeight105 mmLifespanSYearsMounting typeSurfaceLED sourceEpistar		
EAN9340994020419Light Colour3CCTWattage15 WLumen output1260 ImIP rating54CRI80Beam Angle120 DegreesTrim colourBlackLength230 mmHeight105 mmLifespan25000 HoursWarrantySurfaceKounting typeSurfaceLED sourceEpistar	SKU	VBLWL-212-4-CCT
Light Colour3CCTWattage15 WLumen output1260 ImIP rating54CRI80Beam Angle120 DegreesTrim colourBlackLength230 mmHeight105 mmWarranty3 YearsMounting typeSurfaceLED sourceEpistar	Luminaire efficacy	84 lm/W
Wattage15 WLumen output1260 lmIP rating54CRI80Beam Angle120 DegreesTrim colourBlackLength230 mmHeight105 mmLifespan25000 HoursWarrantySurfaceLED sourceEpistar	EAN	9340994020419
Lumen output1260 lmIP rating54IP rating80CRI80Beam Angle120 DegreesTrim colourBlackLength230 mmHeight105 mmLifespan25000 HoursWarrantySurfaceLED sourceEpistar	Light Colour	3CCT
IP rating54IP rating54CRI80Beam Angle120 DegreesTrim colourBlackLength230 mmHeight105 mmLifespan25000 HoursWarranty3 YearsMounting typeSurfaceLED sourceEpistar	Wattage	15 W
CRI80Beam Angle120 DegreesTrim colourBlackLength230 mmHeight105 mmKifespan25000 HoursWarranty3 YearsMounting typeSurfaceLED sourceEpistar	Lumen output	1260 lm
Beam Angle120 DegreesTrim colourBlackLength230 mmHeight105 mmWarranty3 YearsMounting typeSurfaceLED sourceEpistar	IP rating	54
Trim colourBlackLength230 mmHeight105 mmKifespan25000 HoursWarranty3 YearsMounting typeSurfaceLED sourceEpistar	CRI	80
Length230 mmHeight105 mmLifespan25000 HoursWarranty3 YearsMounting typeSurfaceLED sourceEpistar	Beam Angle	120 Degrees
Height105 mmLifespan25000 HoursWarranty3 YearsMounting typeSurfaceLED sourceEpistar	Trim colour	Black
Lifespan25000 HoursWarranty3 YearsMounting typeSurfaceLED sourceEpistar	Length	230 mm
Warranty3 YearsMounting typeSurfaceLED sourceEpistar	Height	105 mm
Mounting typeSurfaceLED sourceEpistar	Lifespan	25000 Hours
LED source Epistar	Warranty	3 Years
	Mounting type	Surface
Material Polycarbonate	LED source	Epistar
rorycarbonace	Material	Polycarbonate
Accessories Comes with complete optional Black Eyelid Frame	Accessories	
Lamp Type LED	Lamp Type	LED
Input voltage 240 Volt AC 50HZ	Input voltage	240 Volt AC 50HZ
Wiring method Hardwire	Wiring method	Hardwire
Weatherproof Weatherproof	Weatherproof	Weatherproof
Box Qty 20	Box Qty	20
Kelvin 3000/4000/6000	Kelvin	3000/4000/6000



Photometric information available upon request.